

Frese Pipe Joiners


Technical Data

Housing/union nut:	Brass
Compression ring:	Stainless steel
O-ring:	EPDM
Sliding washer:	Brass
Finish:	Plain
Pressure class:	PN16
Max. temperature:	120°C
Application:	Repair connector for threaded pipe




Product Programme


Female fitting/union nut

	Frese no.	Size	DN	L mm
	40-1111	3/8"	10	52
	40-1121	1/2"	15	65
	40-1131	3/4"	20	67
	40-1141	1"	25	75
	40-1151	1 1/4"	32	85
	40-1161	1 1/2"	40	95
	40-1171	2"	50	110

Two union nuts

	Frese no.	Size	DN	L mm
	40-1122	1/2"	15	80
	40-1132	3/4"	20	81
	40-1142	1"	25	90
	40-1152	1 1/4"	32	105
	40-1162	1 1/2"	40	120
	40-1172	2"	50	129

Male fitting/union nut

	Frese no.	Size	DN	L mm
	40-1113	3/8"	10	56
	40-1123	1/2"	15	70
	40-1133	3/4"	20	75
	40-1143	1"	25	82
	40-1153	1 1/4"	32	95
	40-1163	1 1/2"	40	102
	40-1173	2"	50	120

Frese A/S assumes no responsibility for errors, if any, in catalogues, brochures, and other printed matter. Frese A/S reserves the right to modify its products without prior notice, including already ordered products, if this does not alter existing specifications. All registered trademarks in this material are the property of Frese A/S. All rights reserved.

Frese A/S
Tel: +45 58 56 00 00
info@frese.dk