


Frese drain valves

Application

Drain valves are used for filling and emptying heating and cooling systems, solar heating systems, district heating systems and drinking water systems**.

Technical data

O-rings:	EPDM
Seal:	PTFE
Pressure Class:	PN10
Max. temperatur	120°C



Product programme



Drain valve male/male incl. strips and cap nut

Frese no.	DN	Dimension	Housing	L-mm	H-mm
35-1130**	15	1/2"	AISI 316 Stainless Steel	57	30.5
35-1137*	15	1/2"	DZR Brass	57	30.5



Drain valve female/male incl. strips and cap nut

Frese no.	DN	Dimension	Housing	L-mm	H-mm
35-1138*	15	1/2"	DZR Brass	51	30.5

* VA-approval

** Approved for drinking water systems in Denmark



Drain valve male/male incl. strips and cap nut

Frese no.	DN	Dimension	Housing	L-mm	H-mm
35-1136	15	1/2"	Brass	67	54



Drain valve female/male incl. strips and cap nut

Frese no.	DN	Dimension	Housing	L-mm	H-mm
35-1135	15	1/2"	Brass	62	54



Cap nut incl. strips

Frese no.	DN	Dimension	Housing
46-5007	6	1/8"	DZR Brass
46-5008	10	3/8"	DZR Brass
46-5009	15	1/2"	DZR Brass
46-5010	20	3/4"	DZR Brass

Frese A/S assumes no responsibility for errors, if any, in catalogues, brochures, and other printed matter. All stated data are subject to tolerances. Frese A/S reserves the right to modify its products without prior notice, including already ordered products, if this does not alter existing specifications. All registered trademarks in this material are the property of Frese A/S. All rights reserved.

Frese A/S
Tel: +45 58 56 00 00
info@frese.dk